

EP6

Plaster Bonding Agent



20L

**Solution to
Plaster Debonding**



EP6 is a special formulated interface bonding agent designed for internal and external plastering works that suit today's construction needs. It is made of emulsify-able vinyl acetate homopolymers coalescing with plasticiser agents and added additives for improving the bonding strength of various substrates, such as smooth concrete walls and ALC/AAC/Light weight blocks.

WHERE TO USE

- Concrete surface.
- Internal skim coating.
- Pre-cast concrete panel.
- Renders base treatment.
- Cement sand block wall.
- Cement rendered surface.
- ALC/ACC/Light weight blocks.
- All cementitious back screeds.
- Internal and external plastering.
- New and old plastered or concrete surfaces.

APPLICATION INSTRUCTIONS

SURFACE PREPARATION

The surface must be structurally sound and clean, free of oil, grease, wax, dust sand, dirt, laitance, paints, efflorescence, curing compounds, loose materials of any type. If the surface is questionable, apply a small test patch of **EP6**. Allow to completely dry and observe for any sign of lifting, wrinkling, peeling or curling. If these occurred, additional surface preparation is recommended. Recommending cleaning methods by washing or high-pressure water jets.

- **EP6** can be applied with paint roller or paint brush.
- Open the original packing and use as it is, do not dilute with water or solvent. Do not add any admixture.
- Never shake and box mixed as to entrap air.
- Apply **EP6** to the treated surface evenly. Thin continuous unbroken film is recommended. Allow **EP6** to dry approximately 30 minutes of drying time, subsequent activities can be carried out.
- Application of plastering, skim coating or renders shall be performed within 10 days provided **EP6** condition is clean, dust free, uncontaminated and intact.
- Do not apply to frozen or frost covered surface or temperature is below 50°F (10°C).
- Do not apply to wet surface where there may be hydrostatic pressure such as retaining walls and swimming pool.

KEEP OUT OF REACH OF CHILDREN

Disclaimer: The information presented is true and accurate to the best of our knowledge, but without any guarantee unless explicitly given. Since the conditions of use are beyond our control we disclaim any liability, including for patent infringement, incurred in connection with the use of these product, date or suggestions.

CAUTIONS

Do not take internally. Avoid contact with skin and eyes. In case of skin contact, wash affected area with soap and water. In case of eye contact, flush with water for 15 minutes and get prompt medical attention.

Product Information		Packaging: 20L
Colour	Blue	
Shelf Life	12 months	
Open Time	14 days	
Drying Time	Approximately 30 minutes after applied, depending on the temperature and humidity (18°C - 45°C)	
Toxicity	Non-toxic	
Fire Hazard	Non-flammable	
Application Method	Can be applied with paint roller or paint brush	
Coverage	Approximately 10 - 15m ² /litre depending on the method of application, temperature, porosity and texture of the substrate/surface	
Storage Conditions	Proper storage in original unopened and undamaged sealed packaging in dry conditions at temperature between +10°C and +37°C. Keep away from direct sunlight, rain and water	
Clean Up	Cleaning may be accomplished with water immediately after use	

